

GENERAL MUNICIPAL CONSENT CONDITIONS

THE APPLICANT FOR THIS PERMIT AGREES TO PROVIDE A MINIMUM OF \$5,000,000 PUBLIC LIABILITY INSURANCE. THE APPLICANT ALSO AGREES AND ACCEPTS FULL RESPONSIBILITY FOR THE PROTECTION OF ALL UTILITIES, PRIVATE PROPERTY AND PERSONS AFFECTED BY THEIR OPERATIONS AND FURTHER AGREES TO INDEMNIFY AND SAVE HARMLESS THE CITY OF VAUGHAN FROM ANY AND ALL DAMAGES OR CLAIMS FOR DAMAGES OR INJURIES OR CLAIMS FOR DAMAGES OR INJURIES OR ACCIDENTS DONE TO OR CAUSED BY THE APPLICANT, OR THE APPLICANT'S EMPLOYEES, AS A RESULT OF THEIR OPERATIONS.

CONSTRUCTION

Maintain a minimum horizontal clearance of 1.00 metre (m) from all adjacent utilities.

Maintain a minimum horizontal clearance and vertical clearance of 1.00 metre (m) from all municipal services and connections (e.g. sanitary, storm and water).

Hand dig within 1.00 metre (m) of all above ground furniture (e.g. fire hydrants, street lights, manholes, pedestals).

NO open excavating/trenching of the driveway(s) is permitted. The driveway(s) are to be directional bored only at a minimum depth of 1.20 metres (m). Unless otherwise stated, all driveway(s) residential or commercial are to remain accessible during construction.

Open excavating/trenching within the drip line of city-owned tree(s) is NOT permitted. Directional bore only at a minimum depth of 1.20 metres (m). Any damages to the city-owned tree(s) are to be reported immediately to the Parks and Forestry Operations Department at (905) 832-8577.

The road allowance must be kept clear of obstructions or debris to avoid hazard or inconvenience to the public.

The general clean up and restoration must commence as soon as possible, and must not be left until the completion of the project.

The Applicant agrees to notify the Utility Coordinator, property owners who may be affected by pending construction and utilities a minimum of forty-eight (48) hours prior to commencing construction.

The Applicant will ensure all personnel working under this permit do so in accordance with the Ministry of Labour's Health and Safety Act for Construction Projects.

Trench Safety must be in accordance with the current Ministry of Labour Standards.

Traffic Control is to be performed in accordance with the Ontario Traffic Manual – Temporary Conditions Book 7.

RESTORATION

All hard surface excavations (e.g. sidewalk removal or road cuts) are to be temporarily restored by the Applicant with a minimum of 75mm of hot mix asphalt and **maintained** by the Applicant until such time the Applicant is able to complete the final restorations.

Construction completed during the winter months (November 1st to March 31st) is to be restored in accordance with the "[Winter Work Boulevard Restoration Policy](#)."

BOULEVARD: The boulevard is to be backfilled to grade with clean, non-frozen native material compacted to 95% standard proctor density to minimize the risk of future settlement. When the weather permits, a minimum of 150mm of native material is to be removed from each excavation and replaced with a minimum of 150mm of screened topsoil and then restored with **NEW** sod. The new sod is to be countersunk to match the existing grades.

CURB: Curb restorations are to be completed in accordance with the City of Vaughan Standard F-2.

ROAD/DRIVEWAY: All road/driveway cuts are to be completed as per the "Trench/Excavation Restoration" detail supplied on the reverse side of the Road Cut Permit.

SIDEWALK: Sidewalk restorations are to be completed in accordance with the City of Vaughan Standard E-1. Please note that the entire sidewalk bay is to be removed and restored with concrete.

SHOULDERS: Shoulders are to be restored with granular 'A,' clear of mud, clay, debris, etc. and to the original cross section and appearance.